

# OS-GIKEN: Multi-Plate Clutch List

OS Multi-Plate Clutch Reference Chart and Example			
Item	Description	Reference	
1	Type of clutch cover	<b>TS</b> - Pressed steel cover <b>TR</b> - Billet aluminum <b>R</b> - Billet aluminum for center hub plate <b>STR</b> - Billet Aluminum	
2	Number of Plates	1 - Single Plate 2 - Twin Plate 3 - Triple Plate 4 - Quadruple Plate	
3	Diameter of Plates	<b>A</b> - 184mm <b>B</b> - 204mm <b>C</b> - 215mm	
4	Remarks	<b>D</b> - Spring Damper <b>W</b> - Heavier Fly Wheel <b>S</b> - Single type diaphragm spring	

  

Model/Engine Type	Type	F/W (kgs.)	Assy (kgs.)
Skyline GTR BNR34	R3C	6.1	15.55
RB26DETT	R4C	6.1	17.35
*OS Clutch Release Movement Alteration Kit is required for installation			
Skyline GTR BCNR33, BNR32	TS2B	6.4	12.8
RB26DETT	TS2BD	6.2	13.35
	TS2CD	6.8	14.5
	TS3B	6.4	14.45
	TS3BW	9.95	18
	R3C	4.9	14.35
	R4C	4.9	16.15
*R32 models before minor change need release bearing and release sleeve specified below:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release sleeve: Nissan 30501-K0401 for TS2B.			
Nissan 30501-U0200 (or 30501-A6801) for TS2(B/C)D. Nissan 30501-A6801 (or U0200) for TS3B.			
Nissan 30501-N1600 for R3C. Nissan 30501-B6000 for R4C.			
*R32 models after minor change (equipped with pull type clutch mechanism; May '93 or later) and R33 models will need OS Clutch Release Movement Alteration Kit to install any of the above.			
OPTIONAL PARTS: Hardened Pivot for R32 models before minor change			
Adjustable Fork kit			
Skyline R31, R32, R33	TS2B	6.4	12.8
RB25DET, RB20	TS2BD	6.2	13.35
	TS2CD	6.8	14.5
	TS3B	6.4	14.45
	TS3BW	9.95	18
	R3C	4.9	14.35
	R4C	4.9	16.15
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release Bearing: OS00-0011 or Nissan 30502-14601. Release sleeve: Nissan 305-K0401 for TS2B.			
Nissan 30501-U0200 (or 30501-A66801) for TS2(B/C)D. Nissan 30501-A6801 (or U0200) for TS3B.			
Nissan 30501-N1600 for R3C. Nissan 30501-B6000 for R4C.			
Optional Parts: Adjustable fork kit			
Skyline DR30	TS2B	5.9	12.3
FJ20ET	TS2BD	6.2	13.35
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100) for TS2B. Nissan 30501-U0200 (or 30501-A6801) for TS2BD			

<b>Skyline HR30 thru GC10</b>	TS2A	4.7	9.8
L6	TS2AD	4.6	10.4
	TS2B	5.9	12.3
	TS2BD	6.1	13.25
	TS3A	4.7	11.1
	TS3B	5.9	13.95
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100)			
for TS2(A/B). Nissan 30501-U0200 (or 30501-A6801) for TS2(A/B) or TS3(A/B).			
<b>Fairlady Z33</b>	TS2BD	7.65	14.8
VQ35DE (NEO)			
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-B6000			
<b>Fairlady Z32</b>	TS2CD	7.3	14.9
VG30DETT	TR2CD	7.3	15.45
	TS3B	7	15.05
	TS3BW	10.3	18.35
	R3C	5.25	14.7
	R4C	5.25	16.5
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release sleeve: Nissan 30501-U0200 (or 305-A6801)			
for TR2CD. Nissan 30501-A6801 (or U0200) for TS3B. Nissan 30501-N1600 for R3C. Nissan 30501-S0100			
(or 30501-K0401) for R4C.			
<b>Fairlady Z32NA</b>	TS2B	6.7	13.1
VG30DE	TS2BD	6.9	14.05
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100)			
for TS2B. Nissan 30501-U0200 (or 30501-A6801) for TS2BD			
<b>Fairlady Z31NA</b>	TS2B	5.8	12.2
VG30DE	TS2BD	5.85	13
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100)			
for TS2B. Nissan 30501-U0200 (or 30501-A6801) for TS2BD			
<b>Fairlady Z31</b>	TS2B	5.9	12.3
VG30ET	TS2BD	6.2	13.35
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100)			
for TS2B. Nissan 30501-U0200 (or 30501-A6801) for TS2BD			
<b>Fairlady S130 thru S30</b>	TS2A	4.7	9.8
L6	TS2AD	4.6	10.4
	TS2B	5.9	12.3
	TS2BD	6.1	13.25
	TS3A	4.7	11.1
	TS3B	5.9	13.95
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100)			
for TS2(A/B). Nissan 30501-U0200 (or 30501-A6801) for TS2(A/B) or TS3(A/B)			
<b>Silvia S15</b>	TS2BD	6.15	13.3
SR20DET	TR2CD	6.7	14.85
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-OH600 (or SO100)			
Also need 8 Genuine Nissan fly wheel bolts (pn: 12315-30P01)			

Silvia PS13, S14	TS2B	6.6	13
SR20DET, SR20DE	TS2BD	6.6	13.95
	TS2CD	7.25	14.85
	TR2CD	7.25	15.4
	R3B	5.15	13.7
	R4B	5.15	14.8
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-B6000 for TS2B.			
Nissan 30501-U0200 (or 30501-A6801) for TS2BD. Nissan 30501-K0500 for R3B. Nissan 30501-U0200 (or 30501-A6801) for R4B.			
Optional Parts: Adjustable fork kit			
Silvia S13	TS2B	5.7	12.1
CA18DET, CA18DE	TS2BD	6.1	13.25
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100) for TS2B. Nissan 30501-U0200 (or 30501-A6801) for TS2BD			
Optional Parts: Adjustable fork kit			
Pulsar RNN14	TS2B	6.8	13.2
SR20DET	R2CD	5.5	13.9
*Original equipped Nissan Sleeve bearing can be used. OS Sleeve bearing kit (enables less pedal effort) is available as an option.			
Bluebird H510, P510	TS2AS	4.8	9.5
L4	TS2A	4.8	9.9
*Release bearing and release sleeve specified below are needed to install any of the above:			
Release bearing: OS00-0011 or Nissan 30502-14601. Release Sleeve: Nissan 30501-K0401 (or SO100) for TS2AS. Nissan 30501-U0200 (or 30501-A6801) for TS2A			
<b>TOYOTA</b>			
<b>Model/Engine Type</b>	<b>Type</b>	<b>F/W (kgs.)</b>	<b>Assy (kgs.)</b>
Supra JZA70	TS2B	6.8	13.2
1JZ-GTE	TS2BD	7	14.15
	TS2CD	7.3	14.9
	TR2CD	7.3	15.45
	TS3BW	9.7	17.75
	R3C	5	11
	R4C	5.4	16.65
		5	11
*OS Clutch Release Movement Alteration Kit is required for installation			
Supra JZA80	TS2CD	5.1	11.1
2JZ-GTE	TR2CD	6.8	14.95
*Sleeve Bearing is included in all above models	TS3B	6.4	14.45
	TS3BW	9.65	17.7
	R3C	6.1	15.75
	R4C	5.4	16.65
*OS Clutch Release Movement Alteration Kit is required for installation			
Optional Parts: *Flywheel bolt set, and Clutch disk center alignment tool			
Supra MA70	TS2B	6.1	12.5
7M-GTE	TS2BD	6.7	13.85
	TS2CD	7	14.6
	TR2CD	7	15.15
	TS3B	6.1	14.15
	TS3BW	8.85	16.9
*OS Clutch Release Movement Alteration Kit is required for installation			

Supra & Soarer	TS2B	5.8	13.95
3S-G			
*This clutch set is thinner than the original equipped clutch system. Adjustment of the clearance by spacer (about 3mm in thickness) between release sleeve and sleeve bearing may be needed.			
Soarer GZ20, Mark II GX71, Chaser GX81	TS2B	5.5	11.9
1G-GT			
*This clutch set is thinner than the original equipped clutch system. Adjustment of the clearance by spacer (about 3mm in thickness) between release sleeve and sleeve bearing may be needed. Optional Sleeve Bearing Set to adjust thickness			
Altezza SXE10	TS2BD	5.8	13.95
3SG			
*OS Sleeve Bearing Set and 8 Genuine Nissan Flywheel bolts (pn:1231504U100) are needed for installation of above clutch.			
MR2 SW20	TS2B	5.9	12.3
3SGT			
*OS Sleeve Bearing set is needed to install the above clutch.			
MR2 SW20 (NA)	TS2B		
3SG			
*OS Sleeve Bearing set is needed to install the above clutch.			
Celica ST185, ST205	TS2B	4.5	12.3
3SGT	R2CD	4.5	12.9
*OS Sleeve Bearing set is needed to install the above clutch.			
Celica ST202 (NA)	TS2B		
3SG	R2CD		
*OS Sleeve Bearing set is needed to install the above clutch. *Super Strut Viscous LSD equipped models should use same clutch as Turbo charged models.			
Levin, Trueno AE86, AE92, AE101	TS2AS	3.6	8.3
4A-G	TS2A	3.6	8.7
	TS2BS	5.05	10.95
	TS2B	5.05	11.45
*When used for AE86, any of these clutch systems are thinner than the original equipped clutch system. Adjustment of the clearance by spacer (about 3mm in thickness) between release sleeve and sleeve bearing may be needed.			
Levin, Trueno AE92, AE101	TS2A	3.6	8.7
4A-GZ	TS2B	5.05	11.45
Starlet EP82	TS2A	4.65	9.75
4E	TS2B	4.3	10.7
<b>MAZDA</b>			
<b>Model/Engine Type</b>	<b>Type</b>	<b>F/W (kgs.)</b>	<b>Assy (kgs.)</b>
RX7 FD3S	TS2B	5.8	12.2
13BT	TS2C	6	13.1
	TS2CW	9.2	16.15
	R2CD	5.8	14.2
	R3A	3.7	10.55
	R3C	4.9	14.35
*Genuine MAZDA counter weight pn: N351-11-521 and 6 bolts pn: 805-27-236 (or 8051-27-235) are needed to install any of the above. OS Clutch Release Movement Alteration Kit is required to install any of the above.			

<b>RX7 FC3S</b>	TS2B	5.8	12.2
13BT	TS2C	6	13.1
	TS2CW	9.2	16.15
	R2CD	5.8	14.2
	R3A	3.7	10.55
	R3C	4.9	14.35
*Genuine MAZDA counter weight pn: N327-11-521A and 6 bolts pn: 805-27-236 (or 8051-27-235) for chassis No. 0 to 20000 (before minor change) are needed to install any of the above.			
*Use genuine MAZDA counter weight pn: N351-11-521 and 6 bolts pn: 805-27-236 (or 8051-27-235) for chassis No. 20001 and on (after minor change) are needed to install any of the above.			
Optional Parts: Reinforced sleeve bearing kit and adjustable fork kit			
<b>RX7 SA22C</b>	TS2AS	5.1	9.8
12A	TS2A	5.1	10.2
	TS2BS	5.25	11.15
	TS2B	5.25	11.65
*If thermal reactor and/or catalytic converter is equipped, genuine MAZDA counter weight (pn:1883-11-751A) and 6 bolts (pn:8051-27-235 or 236) are needed to install any of the above. If 6PI and/or turbo charger is equipped, use genuine MAZDA counter weight (pn:N351-11-521A) and 6 bolts (pn:805-27-235 or 236) are needed to install any of the above.			
<b>Roadstar NA6CE, NA8C</b>	TS2AS	4.1	8.8
B6, BP8	TS2A	4.1	9.2
	TS2BS	4.9	10.8
	TS2B	4.9	11.3
*OS Release Sleeve Bearing Set is required to install any of the above.			
<b>RX-8 SE3P</b>	TS2B	5.8	12.2
13B-MPS	TS2C	6	13.1
	TS2CW	9.2	16.15
	R2CD	5.8	14.2
	R3A	3.7	10.55
	R3C	4.9	14.35
*Sleeve Bearing			
<b>mitsubishi</b>			
<b>Model/Engine Type</b>	<b>Type</b>	<b>F/W (kgs.)</b>	<b>Assy (kgs.)</b>
<b>Lancer Evolution I thru III CD9A, CE9A</b>	TS2B	5.8	12.2
	R2CD	6.05	14.45
*OS Release Sleeve Bearing Set is required to install any of the above.			
<b>Lancer Evolution VII+ CN9A, CP9A</b>	TS2B	5.3	11.9
4G63	R2CD	5.2	13.6
*OS Clutch Release Movement Alteration Kit is required to install any of the above. Genuine Mitsubishi Inner Kit (pn:MD977130) is required for use with OS Clutch Release Movement Alteration Kit *MITSUBISHI parts (pn:MD725220) or main drive shaft of MAZDA FC3S can be used as a clutch disk center alignment tool			
<b>VR4 E38A, E39A</b>	TS2B	5.9	12.3
4G63			
*OS Release Sleeve Bearing Set is required to install any of the above. Before order ing OS Release Bearing Set, please make sure if you model was a minor change model or not, as specifications differ.			
<b>3000GT Z16A Turbo</b>	TS2C	6.5	13.45
6A72			
*OS Release Sleeve Bearing Set is required to install any of the above. *MITSUBISHI parts (pn:MD725220) or main drive shaft of MAZDA FC3S can be used as a clutch disk center alignment tool			

Legnum VR4 E-EC5W (VR4)	R2C	5.4	13.15
6A13	R2CD	5.4	13.8
*OS Clutch Release Movement Alteration Kit is required to install any of the above.			
<b>SUBARU</b>			
<b>Model/Engine Type</b>	<b>Type</b>	<b>F/W (kgs.)</b>	<b>Assy (kgs.)</b>
Impreza	TS2B	7.2	13.6
EJ20	R2CD	5.25	13.65
*OS Clutch Release Movement Alteration Kit is required to install any of the above.			
Optional Parts: Clutch Disk Center Alignment Tool			
<b>HONDA</b>			
<b>Model/Engine Type</b>	<b>Type</b>	<b>F/W (kgs.)</b>	<b>Assy (kgs.)</b>
NSX NA1 thru NA2	R2C	5.35	13.1
C30A	R2CD	5.35	13.75
*OS Clutch Release Movement Alteration Kit is required to install any of the above.			
S2000	TS2B	4.1	10.85
F20C			
*OS Clutch Release Movement Alteration Kit is required to install any of the above.			
Prelude BB1, BB4	TS2B	6.7	13.1
H22A			
*OS Release Sleeve Bearing Set is required to install any of the above.			
CRX, Civic EF8, EF9	TS2AS	4.7	9.4
B16A	TS2A	4.7	9.8
*OS Release Sleeve Bearing Set is required to install any of the above.			
Civic EG6, EK4, EK9, DC2	TS2AS	4.7	9.4
B16A, B16B, B18C	TS2A	4.7	9.8
*OS Release Sleeve Bearing Set is required to install any of the above.			
<b>LAMBORGHINI</b>			
<b>Model/Engine Type</b>	<b>Type</b>	<b>F/W (kgs.)</b>	<b>Assy (kgs.)</b>
Countach/Diablo	R3CS		
	TR2CD		
*For push type OE clutch - Sleeve Bearing required; for pull type conversion kit required			